

Howells Glazing Systems

S1 Single / Dual Rack Actuators with Slave Drive



Technical Specification

	Rack 230v	Rack 24v
Voltage Supply	230v	24v
Thrust Force	650N 1000mm max. 350N	750N 1000mm max. 350N
Traction Force	650N	750N
Stroke	180mm, 230mm, 350mm, 550mm, 750mm, 1000mm	180mm, 230mm, 350mm, 550mm, 750mm, 1000mm
Absorbed Current	0.1 amp	1 amps
Time Rating	50%	50%
Limit Stop	electronic	electronic
Safety Stop	electronic	electronic
Wiring	4 core	2 core
Speed	~ 8 mm/s	~ 8 mm/s
Double Insulated	no	no
Protection Class	IP55	IP55
Parallel Connection Option	yes	yes
Weight	2kg	2kg
Colours Available	silver	silver

Product Summary

- 12mm for 750mm/1000mm square rack transmission.
- Noiseless operation
- All the actuators can be used in the Dual-Rack version by adding connecting rods and rack groups for the installation in particularly large windows
- High protection from atmospheric agents

230mm Stoke £ 140.00 + VAT

350mm Stoke £ 142.00 + VAT

550mm Stoke £ 150.00 + VAT

750mm Stoke £ 165.00 + VAT

(Delivery Not Included)

July 2006

Forge Lane, Cradley. Heath West Midlands. B645AL. Tel. 01384 820060 Fax. 01384 860150
Email:- sales@howellsglazing.co.uk Web:- www.howellsglazing.co.uk